

---

## ABS-CSF

### Convoluted microwave broadband foam absorber

ABS-CSF is a series of 3D shaped light weight foam absorber. The front side has a convoluted shape which improves its RF-performance level for the higher frequency range. Due to its specific shape the reflectivity level will not degrade for higher angles of incidence of the signal. We can supply 3 different types respectively CSF-3, CSF 4 and CSF-6 with thickness of respectively : 3, 4 and 6 inch.

#### Applications :

- ABS-CSF are often mounted on removable walls in test areas
- Installation in anechoic test boxes or to line area's nearby RF-systems to suppress reflections.
- Covering of metal structures in anechoic test environments

#### Specifications :

Max. service temperature : +90°C

Power handling : 1,5 Kw/m<sup>2</sup>

Frequency range typically above 3 GHz up to 40 GHz

#### Properties :

ABS-CSF is specified by its reflectivity level for each type of thickness.

Reflectivity levels start at -20dB at lowest frequency and thickest material up to -40dB in the higher frequency range.

#### Availability :

Besides standard outside dimensions 610x610mm also specific or customized sizes and shapes can be supplied. ABS-CSF can also be supplied with a self-adhesive tape. The front side is painted white, however for mm-wave applications we recommend to apply the material unpainted as the paint will degrade the reflectivity level.

---

The information in this technical data sheet is believed by ABS Technics to be accurate and reliable. ABS Technics makes no representations or warranties of any kind on this data. All specifications can be subject to change without any notice. ABS Technics shall not be liable for incidental or consequential damages of any kind due to the usage of their material. All ABS Technics products are sold pursuant to our 'Terms and Conditions of Sale'.